



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Superflor

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Superflor			
Type	Hair			
Yarn	82.5% Nylon, 17.5% Polyester			
Standard Backing	Graphlar®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC3			
Total Thickness	7.8 mm ± 0.5 mm			
Size	50 x 50 cm - 5 m ² Box			
Colourway	9008 Grey	9023 Mid Brown	9101 Yippee	9102 Fruity
	9103 Magic	9106 Electra	9155 Raven	9156 Oceanus
	9157 Lagoon Blue	9162 Primavera	9164 Pacific Sunset	9165 Pineforest
	9169 Siberian Frost	9174 Arctic Dawn	9191 Seville Passion	9194 Berber Beige
	9198 Irish Coffee	9199 Buffalo		
Method of laying	Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465