



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

The Scandinavian Collection

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	The Scandinavian Collection			
Type	Microtufted loop pile			
Yarn	100% Solution Dyed Nylon contains recycled content			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	4.4 mm ± 0.5 mm			
Size	50 x 50 cm - 5 m ² Box			
Colourway	303100 Bergen	303101 Helsinki	303102 Reykjavik	303103 Stockholm
	303105 Malmo	303112 Copenhagen	303113 Nordkapp	303118 Hekla
	303119 Visby	303120 Torshavn	303121 Narvik	303122 Kirkenes
Method of laying	Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465