



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Touch of Timber

| | | | | |
|----------------------------------|---|---------------|---------------|------------------|
| Location | Heavy use areas. Office, retail, hospitality, leisure and educational areas. | | | |
| Base | Please refer to Interface installation guide for details of suitability. | | | |
| Preparation | Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. | | | |
| Fabricated Underlay | Should be laid where required over existing timber bases. | | | |
| Carpet Tiles | | | | |
| Manufacturer | Interface | | | |
| Product Reference | Touch of Timber | | | |
| Type | Microtufted loop pile | | | |
| Yarn | 100% Recycled Solution Dyed Nylon | | | |
| Standard Backing | Graphlex® | | | |
| BS EN 1307 classification | | | | |
| Category | Type 1 | | | |
| Level of use class | Heavy Contract, class 33 | | | |
| Luxury rating class | LC1 | | | |
| Total Thickness | 5.1 mm ± 0.5 mm | | | |
| Size | 25 x 100 cm - 5 m ² Box | | | |
| Colourway | 606211 Balsa | 606212 Bamboo | 606213 Oak | 606214 Elm |
| | 606215 Silver Birch | 606216 Ash | 606217 Maple | 606218 Sycamore |
| | 606219 Blue Spruce | 606220 Olive | 606221 Walnut | 606222 Blackwood |
| Method of laying | Herringbone, Ashlar. Install using TacTiles® for a glue-free installation | | | |

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690