



Touch of Timber

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.												
Base	Please refer to Interface installation guide for details of suitability.												
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.												
Fabricated Underlay	Should be laid where required over existing timber bases.												
Carpet Tiles													
Manufacturer	Interface												
Product Reference	Touch of Timber												
Type	Microtufted loop pile												
Yarn	100% Recycled Solution Dyed Nylon												
Standard Backing	Graphlex®												
BS EN 1307 classification													
Category	Type 1												
Level of use class	Heavy Contract, class 33												
Luxury rating class	LC1												
Total Thickness	5.3 mm ± 0.5 mm												
Size	25 x 100 cm - 5 m ² Box												
Colourway	<table border="0"> <tr> <td>4191001 Balsa</td> <td>4191002 Bamboo</td> <td>4191003 Oak</td> <td>4191004 Elm</td> </tr> <tr> <td>4191005 Silver Birch</td> <td>4191006 Ash</td> <td>4191007 Maple</td> <td>4191008 Sycamore</td> </tr> <tr> <td>4191009 Blue Spruce</td> <td>4191010 Olive</td> <td>4191011 Walnut</td> <td>4191012 Blackwood</td> </tr> </table>	4191001 Balsa	4191002 Bamboo	4191003 Oak	4191004 Elm	4191005 Silver Birch	4191006 Ash	4191007 Maple	4191008 Sycamore	4191009 Blue Spruce	4191010 Olive	4191011 Walnut	4191012 Blackwood
4191001 Balsa	4191002 Bamboo	4191003 Oak	4191004 Elm										
4191005 Silver Birch	4191006 Ash	4191007 Maple	4191008 Sycamore										
4191009 Blue Spruce	4191010 Olive	4191011 Walnut	4191012 Blackwood										
Method of laying	Herringbone, Ashlar. Install using TacTiles® for a glue-free installation												

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465