



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Touch & Tones 101

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Touch & Tones 101			
Type	Level loop pile			
Yarn	100% Recycled Nylon			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.6 mm ± 0.5 mm			
Size	50 x 50 cm - 5 m ²			
Colourway	659101 Silver	659102 Neutral Grey	659103 Linen	659104 Greige
	659105 Elephant	659106 Taupe	659107 Tobacco	659108 Black
	659109 Orange	659110 Red	659111 Bougainvillea	659112 Grape
	659113 Ultra Marine	659114 Turquoise	659115 Lemonade	659116 Moss
Method of laying	Monolithic. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690