



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Touch & Tones 101

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Touch & Tones 101
Type	Level loop pile
Yarn	100% Recycled Nylon
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	6.2 mm ± 0.5 mm
Size	50 x 50 cm - 5 m ²
Colourway	4174001 Silver 4174002 Neutral Grey 4174003 Linen 4174004 Greige 4174005 Elephant 4174006 Taupe 4174007 Tobacco 4174008 Black 4174009 Orange 4174010 Red 4174011 Bougainvillea 4174012 Grape 4174013 Ultra Marine 4174014 Turquoise 4174015 Lemonade 4174016 Moss
Method of laying	Monolithic. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465