



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Touch & Tones 102

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Touch & Tones 102
Type	Structured loop pile
Yarn	100% Recycled Nylon
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC3
Total Thickness	7.8 mm ± 0.5 mm
Size	50 x 50 cm - 4 m ² Box
Colourway	4175001 Silver 4175002 Neutral Grey 4175003 Linen 4175004 Greige 4175005 Elephant 4175006 Taupe 4175007 Tobacco 4175008 Black 4175009 Orange 4175010 Red 4175011 Bougainvillea 4175012 Grape 4175013 Ultra Marine 4175014 Turquoise 4175015 Lemonade 4175016 Moss
Method of laying	Monolithic. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465