



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Touch & Tones 103

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Touch & Tones 103
Type	Cut pile tufted
Yarn	100% Nylon
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC5
Total Thickness	10.2 mm ± 0.5 mm
Size	50 x 50 cm - 3 m ² Box
Colourway	4176001 Silver 4176002 Neutral Grey 4176003 Linen 4176004 Greige 4176005 Elephant 4176006 Taupe 4176007 Tobacco 4176008 Black 4176009 Orange 4176010 Red 4176011 Bougainvillea 4176012 Grape 4176013 Ultra Marine 4176014 Turquoise 4176015 Lemonade 4176016 Moss
Method of laying	Monolithic. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465