



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Touch & Tones 103

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Touch & Tones 103			
<b>Type</b>	Cut pile tufted			
<b>Yarn</b>	100% Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC5			
<b>Total Thickness</b>	10.4 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm - 3 m <sup>2</sup> Box			
<b>Colourway</b>	659301 Silver	659302 Neutral Grey	659303 Linen	659304 Greige
	659305 Elephant	659306 Taupe	659307 Tobacco	659308 Black
	659309 Orange	659310 Red	659311 Bougainvillea	659312 Grape
	659313 Ultra Marine	659314 Turquoise	659315 Lemonade	659316 Moss
<b>Method of laying</b>	Monolithic. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690