



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Transformation

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Transformation			
Type	Pattern loop pile			
Yarn	100% Solution Dyed Nylon contains recycled content			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.3 mm ± 0.5 mm			
Size	50 x 50 cm - 4 m ² Box			
Colourway	1628004 Meadow	1628010 Fern	1628011 River	1628013 Steppe
	1628014 Desert	1628016 Tropics	1628019 Wadi	1628020 Amazon
	1628024 Lava	1628025 Pasture	1628026 Moorland	1628029 Plantation
	1628063 Shell	1628064 Clay	1628065 Gabbro	1628066 Pewter
	1628067 Nightshade	1628068 Oatmeal	1628069 Manilla	1628070 Parchment
	1628072 Saxon	1628073 Baring	1628074 Azure	1628075 Truffle
Method of laying	Non Directional. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT
Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface®