



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Transformation

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Transformation			
Type	Pattern loop pile			
Yarn	100% Solution Dyed Nylon contains recycled content			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.5 mm ± 0.5 mm			
Size	50 x 50 cm - 4 m ² Box			
Colourway	304187 Meadow	304196 Fern	304197 River	345502 Steppe
	345504 Desert	345506 Tropics	345511 Wadi	345514 Amazon
	345518 Lava	345519 Pasture	345520 Moorland	345523 Plantation
	345530 Shell	345531 Clay	345532 Gabbro	345533 Pewter
	345534 Nightshade	345535 Oatmeal	345536 Manilla	345537 Parchment
	345539 Saxon	345540 Baring	345541 Azure	345542 Truffle
Method of laying	Non Directional. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690