



Twist & Shine Mirco

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.	
Base	Please refer to Interface installation guide for details of suitability.	
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.	
Fabricated Underlay	Should be laid where required over existing timber bases.	
Carpet Tiles		
Manufacturer	Interface	
Product Reference	Twist & Shine Mirco	
Type	Microtufted loop pile	
Yarn	100% Recycled Solution Dyed Nylon	
Standard Backing	Graphlex®	
BS EN 1307 classification		
Category	Type 1	
Level of use class	Heavy Contract, class 33	
Luxury rating class	LC1	
Total Thickness	5.1 mm ± 0.5 mm	
Size	50 x 50 cm - 5 m ²	
Colourway	4190001 Stone Micro	4190002 Smoke Micro
	4190005 Cloud Micro	4190007 Thunder Micro
	4190008 Midnight Micro	4190009 Spruce Micro
Method of laying	Monolithic, Quarter Turn. Install using TacTiles® for a glue-free installation	

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465