



Unity

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.																
Base	Please refer to Interface installation guide for details of suitability.																
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.																
Fabricated Underlay	Should be laid where required over existing timber bases.																
Carpet Tiles																	
Manufacturer	Interface																
Product Reference	Unity																
Type	Pattern loop pile																
Yarn	100% Solution Dyed Nylon contains recycled content																
Standard Backing	Graphlex®																
BS EN 1307 classification																	
Category	Type 1																
Level of use class	Heavy Contract, class 33																
Luxury rating class	LC2																
Total Thickness	5.9 mm ± 0.5 mm																
Size	50 x 50 cm - 4 m ² Box																
Colourway	<table border="0"> <tr> <td>1136004 Carbon</td> <td>1130655 Bone</td> <td>1136056 Fossil</td> <td>1136002 Graphite</td> </tr> <tr> <td>1136058 Husk</td> <td>1136059 Pebble</td> <td>1136007 Pumice</td> <td>1136065 Lime</td> </tr> <tr> <td>1136062 Lagoon</td> <td>1136001 Crystal</td> <td>1136064 Dandelion</td> <td></td> </tr> <tr> <td>1136003 Boulder</td> <td></td> <td></td> <td></td> </tr> </table>	1136004 Carbon	1130655 Bone	1136056 Fossil	1136002 Graphite	1136058 Husk	1136059 Pebble	1136007 Pumice	1136065 Lime	1136062 Lagoon	1136001 Crystal	1136064 Dandelion		1136003 Boulder			
1136004 Carbon	1130655 Bone	1136056 Fossil	1136002 Graphite														
1136058 Husk	1136059 Pebble	1136007 Pumice	1136065 Lime														
1136062 Lagoon	1136001 Crystal	1136064 Dandelion															
1136003 Boulder																	
Method of laying	Quarter Turn, Ashlar. Install using TacTiles® for a glue-free installation																

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465