

## NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## **Composure Edge**

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.	
Base	Please refer to Interface installation guide for details of suitability.	
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.	
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.	
Carpet Tiles		
Manufacturer	Interface	
Product Reference	Composure Edge	
Туре	Tufted Patterned Structured Loop Pile	
Yarn	100% Solution Dyed Nylon contains recycled content	
Standard Backing	Graphlex <sup>®</sup>	
Backing Options	CircuitBac Green & SONE®	
BS EN 1307 classification		
Category	Type 1	
Level of use class	Heavy Contract, class 33	
Luxury rating class	LC2	
Total Thickness	6.1 mm ± 0.5 mm	
Size	50 x 50 cm standard size, 4m <sup>2</sup> per box	
Colourway	4274001427400242740034274004Pewter/ IsolationWave/ IsolationOlive/ SeclusionSunburst/ Seclusion4274005427400642740074274008Abyss/DiffuseSapphire/ DiffuseAubergine/ SolitudeBerry/ Solitude	sion
Method of laying	Non Directional Install using TacTiles® for a glue-free installation	

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

