



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Works Fluid

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.	
Base	Please refer to Interface installation guide for details of suitability.	
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.	
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.	
Carpet Tiles		
Manufacturer	Interface	
Product Reference	Works Fluid	
Type	Tufted Patterned Structured Loop Pile	
Yarn	100% Solution Dyed Nylon	
Standard Backing	Graphlex®	
BS EN 1307 classification		
Category	Type 1	
Level of use class	Heavy Contract, class 33	
Luxury rating class	LC1	
Total Thickness	7.1 mm ± 0.5 mm	
Size	25 x 100 cm standard size, 5m ² per box	
Colourway	4285001 Ebony	4285002 Storm
	4285003 Concrete	4285004 Dove
	4285005 Shadow	4285006 Taupe
	4285007 Drizzle	4285008 Denim
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation	

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#). For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465