



Yuton 104

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Yuton 104
Type	Pattern loop pile
Yarn	100% Nylon
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	6.2 mm ± 0.5 mm
Size	50 x 50 cm - 4 m ² Box
Colourway	305568 Cloud 305569 Slate 305570 Thunder 305571 Charcoal 305572 Whirl Pool 305573 Petrol 305574 Ember 305575 Crimson 305576 Pasture 305577 Stone 305578 Mink 305579 Fern
Method of laying	Ashlar, Non Directional, Quarter Turn. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690