



## Yuton 104

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Yuton 104			
<b>Type</b>	Pattern loop pile			
<b>Yarn</b>	100% Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC1			
<b>Total Thickness</b>	6 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm - 4 m <sup>2</sup> Box			
<b>Colourway</b>	305568 Cloud	305569 Slate	305570 Thunder	305571 Charcoal
	305572 Whirl Pool	305573 Petrol	305574 Ember	305575 Crimson
	305576 Pasture	305577 Stone	305578 Mink	305579 Fern
<b>Method of laying</b>	Ashlar, Non Directional, Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465