



Yuton 104

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Yuton 104			
Type	Pattern loop pile			
Yarn	100% Nylon			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	6.2 mm ± 0.5 mm			
Size	50 x 50 cm - 4 m ² Box			
Colourway	305568 Cloud	305569 Slate	305570 Thunder	305571 Charcoal
	305572 Whirl Pool	305573 Petrol	305574 Ember	305575 Crimson
	305576 Pasture	305577 Stone	305578 Mink	305579 Fern
Method of laying	Ashlar, Non Directional, Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690