



Yuton 105

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Yuton 105
Type	Pattern loop pile
Yarn	100% Nylon
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	5.9 mm ± 0.5 mm
Size	50 x 50 cm - 4 m ² Box
Colourway	305580 Driftwood 305581 Tuscan 305582 Shadow 305583 Slate Grey 305584 Graphite 305585 Smoky Black 305586 Sepia 305587 Bistre 305588 Sky 305589 Cerulean 305590 Kiwi 305591 Indian Red
Method of laying	Ashlar, Monolithic. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465