

## **INTERTAC PLUS ADHESIVE**

### **PRODUCT DESCRIPTION**

Intertac Plus Adhesive is a Solvent Free, Low Odour, Low VOC Pressure Sensitive adhesive formulated for installing Interface Glasbac Carpet Tiles and Interface LVT plank and square tiles.

### **SURFACE PREPARATION**

To be in accordance with the current Australian Standard "Floor Coverings - 1884-2012 Resilient Sheet & Tiles - Laying & Maintenance Practices" or Australian Standard 2455.2.2007 "Textile Floor Coverings - Installation Practice".

All surfaces to be bonded shall be absorbent, dry, smooth, sound and clean. Subfloors must also be free of wax, grease, paint, previously used adhesive, polish, PVC based membranes and hydrostatic pressure.

All concrete floors should be tested for moisture content in accordance the above Australian Standards prior to the undertaking surface preparation or installation of floorcoverings.

The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C.

It is recommended that highly absorbent concrete subfloors be primed with Roberts R400 floor and wall primer prior to the application of adhesive.

### **APPLICATION & SPREAD RATE**

Intertac Plus Pressure Sensitive Adhesive may be applied using different techniques, depending on the installation.

1. For securing Interface Glasbac Carpet tiles we recommend the use a log nap roller with a pile height of no less than 10mm is recommended.  
The use of a long nap roller with a pile height of no less than 10mm can achieve an approx spread rate of 10-14 square metres per litre.  
In some cases a higher spread rate on application can be achieved when applied over low absorbent substrates.  
Alternatively applying adhesive with a 1.6mm x1.6mm notched "V1" notched trowel will achieve up to 5 square metres per litre.
2. For securing Interface LVT plank and square tiles to a sub floor a 1.6mm x1.6mm "V1" notched trowel is recommended. Coverage up to 5 square meters per litre.

Intertac Plus adhesive is used in dry mode, allow the adhesive to dry and become clear, this will limit the transfer of the adhesive to the back of the carpet tiles therefore enabling them to be relayed or repositioned with a clean backing.

A stronger bond can be achieved by laying the material into the adhesive film just prior to it drying completely, this will cause some transfer onto the back of the material.

### **CLEAN UP**

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using R550 Latex/Acrylic Adhesive Remover applied to a damp cloth then rubbed gently over the dried adhesive or alternatively please use AFTEK Handy Wipes.

### **SHELF LIFE**

12 -14 months in unopened containers stored out of direct sunlight.

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

### **RLA POLYMERS PTY LTD**

ACN 004 739 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au

**STORAGE**

Keep in well ventilated areas stored out of direct sunlight.

**CONTAINER SIZES**

15 litre plastic containers

**SAFETY & HANDLING**

A Safety Data Sheet is available on request.

**FIRST AID**

For advice contact a Poison Information Centre (Australia PH: 13 11 26 , New Zealand PH: 0800 764 766) or a doctor at once. A Material Safety Data Sheet is available on request.

*Issued: November 2018*

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

**RLA POLYMERS PTY LTD**

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia  
P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: [info@rlapolymers.com.au](mailto:info@rlapolymers.com.au) • Web: [www.rlagroup.com.au](http://www.rlagroup.com.au)