

ENVIRONMENTAL PRODUCT DECLARATION

MODULAR CARPET

INTERFACE ASIA PACIFIC - THAILAND
GLASBAC®, TYPE 6 NYLON



Interface®

Interface is the world's largest manufacturer of commercial carpet tile.

For over 40 years Interface has consistently led the industry through design and innovation and is a world leader in environmental sustainability. We are well along the path to achieving Mission Zero®, our promise to eliminate any negative impact we have on the environment by 2020. We are committed to making our progress transparent.

At Interface, we believe Life Cycle Assessment is critical for evaluating the environmental impacts of our products and that the LCA based Environmental Product Declaration is the best way to provide full disclosure of those impacts to our customers.

Interface was one of the first companies to develop EPDs for all of our products manufactured globally, and we continue to remain committed to providing this level of transparency to our customers, partners and the industry at large.

For more information visit
www.interface.com



Interface®

Interface Asia Pacific - Thailand
 Modular Carpet on GlasBac®
 Nylon 6 Styles

According to ISO 14025

This declaration is an environmental product declaration (EPD) in accordance with ISO 14025. EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycle. Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc. Accuracy of Results: EPDs regularly rely on estimations of impacts, and the level of accuracy in estimation of effect differs for any particular product line and reported impact. Comparability: EPDs are not comparative assertions and are either not comparable or have limited comparability when they cover different life cycle stages, are based on different product category rules or are missing relevant environmental impacts. EPDs from different programs may not be comparable.



PROGRAM OPERATOR	UL Environment
DECLARATION HOLDER	Interface, Inc.
DECLARATION NUMBER	4787521006.109.1
DECLARED PRODUCT	Interface Asia Pacific - Thailand modular carpet on GlasBac, Nylon 6 styles
REFERENCE PCR	IBU and UL Environment. PCR for Building-Related Products and Services - Part A: Calculation rules for the LCA and Requirements Project Report, (IBU/ULE, Version 1.306.19.2014) IBU. Part B: Requirements on the EPD for Floor coverings (IBU, V1.6, 07.30.2014)
DATE OF ISSUE	November 1, 2016
PERIOD OF VALIDITY	5 Years
CONTENTS OF THE DECLARATION	Product definition and information about building physics Information about basic material and the material's origin Description of the product's manufacture Indication of product processing Information about the in-use conditions Life cycle assessment results Testing results and verifications
The PCR review was conducted by:	UL Environment Review Panel IBU Independent Expert Committee (SRV) epd@ulenvironment.com
This declaration was independently verified in accordance with ISO 14025 by Underwriters Laboratories <input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL	 Wade Stout, UL Environment
This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:	 Thomas Gloria, Industrial Ecology Consultants

ENVIRONMENTAL PRODUCT DECLARATION

Interface®

Interface Asia Pacific - Thailand
Modular Carpet on GlasBac®
Nylon 6 Styles

According to ISO 14025

Product

Product description

This Environmental Product Declaration covers all styles and patterns of modular carpet on GlasBac® recycled backing with recycled Nylon yarn. The products are manufactured in Chonburi Thailand. The products range in yarn weight from 441 to 1424 grams per square meter. A medium yarn weight of 678 grams per square meter is reported and the Global Warming Potential of all additional product yarn weights are reported.

Application

Modular installation of textile floor covering in commercial buildings

Technical Data

Name	Value	Unit
Product Form	Tiles	-
Type of Manufacture	Tufted	-
Yarn Type	Nylon	-
Secondary Backing	Vinyl composite	-
Total Weight	4189	grams/m ²
Total Yarn Weight	678	grams/m ²

Delivery Status

Available in a range of tile and plank sizes, mostly commonly 0.5 x 0.5 meter squares and 1.0 x 0.25 meter planks.

Base Materials

Component	Material	Mass %
Yarn	Post-consumer recycled Nylon	8
	Pre-consumer recycled Nylon	8
Primary backing	Pre-consumer recycled polyester	3
Precoat backing	Ethylene vinyl acetate copolymer	5
	Pre-consumer recycled limestone	15
Stabilization layer	Fiberglass	2
Secondary backing	Di-isononyl phthalate	9
	Pre-consumer recycled limestone	36
	Polyvinyl chloride	13

Manufacture

Yarns are tufted into a primary backing fabric. A precoat backing is applied to the reverse side of the tufted face cloth to fix the yarns in place then a secondary backing which includes a stabilization layer is applied. The product is then cut into tiles and packaged.

Environment and health during manufacturing

Environment



ENVIRONMENTAL PRODUCT DECLARATION

Interface®

Interface Asia Pacific - Thailand
Modular Carpet on GlasBac®
Nylon 6 Styles

According to ISO 14025

- ISO 14001 Environmental Management System
- Compliance with Public Health and Environment requirements of NSF104 Sustainability Assessment for Carpet

Packaging

Carpet tiles are packaged in boxes made with 100% post-consumer recycled cardboard. Packaging waste should be reused or sent local cardboard recycling facilities.

Conditions of use

During the reference service life of the carpet, it should be cleaned in accordance with the product warranty instructions including vacuuming and extraction cleaning. The frequency is dependent upon the expected foot traffic and local conditions.

Environment and health during use

Product has low VOC emissions as indicated by compliance with the Carpet and Rug Institute's Green Label Plus requirements. The current certificate can be found at <http://www.carpet-rug.org/glp-carpet-products.html>

Reference service life

The reference service life of this product is 15 years based on product warranty.

Extraordinary effects

Fire

Name	Value
Radiant panel (ASTM E-648)	Class 1
Smoke density (ASTM E-662)	< 450

Water: The product's backing is impervious to water, protecting the subfloor from leaks and spills. Exposure to flooding for long periods may result in damage to the product.

Mechanical destruction: The product is intended for commercial applications with heavy wear (CRI Test method 101 Appearance Retention Rating). Performance requires proper installation according to Interface installation guidelines.

Re-use phase

The modular aspect of the product along with Tactile installation as opposed to glue-down methods allows for easy re-use of the product. The product is intended to be recycled through Interface's ReEntry 2.0 process.

Disposal

At end of life the product should be returned to Interface through Interface's ReEntry 2.0 process by contacting Interface (Thailand) Co., Ltd. 700/117 M.1 Amata Nakorn Industrial Estates, Baankao, Panthong, Chonburi 20160, Thailand, t:+66(0)38 214303-5. Disposal in municipal landfill or commercial incineration facilities is permissible in accordance with local regulations.

LCA: Calculation rules

ENVIRONMENTAL PRODUCT DECLARATION

Interface®

Interface Asia Pacific - Thailand
Modular Carpet on GlasBac®
Nylon 6 Styles

According to ISO 14025

Declared unit

Name	Value	Unit
Declared unit	1	m ²
Conversion factor to 1 kg	0.239	-
Mass	4.189	kg/m ²

System boundary

This study includes all relevant cradle-to-grave environmental information for the life cycle of one square meter of carpet. The analysis period for each module is one fiscal year. The system boundaries include:

A1-A3 Product stage

- A1 raw material extraction and processing, and processing of recycled materials
- A2 transport to the Interface factory and inter-company transport between buildings
- A3 manufacturing at Interface including materials, packaging, energy, and waste disposal or recycling

A4-A5 Construction stage

- A4 transport to installation site
- A5 installation including ancillary materials required for installation and trim-waste disposal

B2 Maintenance: Includes the energy for vacuuming and wet extraction cleaning and also the production and transport of cleaning agents. The treatment of the waste water from extraction cleaning is included.

C2 Transport of waste to local disposal

C4 Disposal

Estimates and assumptions

The datasets for materials upstream from Interface manufacturing are a combination of information from the GaBi database and supplier provided datasets. Inventories for all materials are not available and when unavailable, conservative proxy datasets were chosen based on similarity of material.

Cut-off criteria

As dictated by the Part A: Calculation rules for the life cycle assessment and requirements, the cut-off criteria is less than 1% for energy use and less than 1% of total mass per unit process, the sum of which shall not exceed 5% of either energy or mass. If a flow met the cut-off criteria for exclusion, yet was thought to have significant environmental impact, then it was included.

Background data

The datasets for materials upstream from Interface manufacturing are a combination of information from the GaBi database version 6.116 in 2016 and supplier provided datasets. The supplier provided data adds significant confidence to the LCA result because it is geographically and technologically specific to the Interface materials. This supplier specific data covers a majority of the environmental impact of the product and includes the Nylon yarn, tufting primary,

Interface®

Interface Asia Pacific - Thailand
 Modular Carpet on GlasBac®
 Nylon 6 Styles

According to ISO 14025

fiberglass, plasticizer, filler, and product packaging.

Data quality

The data quality ranges from good to very good. The temporal quality of the data is very good with the Interface data being from 2015, the supplier specific data ranging from 2012 to 2016 and the GaBi background data being from 2016.

Period under review

The data collection and the product described are an average product manufactured in 2015.

Allocation

Where relevant, the background data incorporates some allocation such as in the power mix. There are no co-products produced in the process, so the LCA model does not include allocation. No credits were taken for recycling of production waste.

Comparability

A comparison or an evaluation of EPD data is only possible if all of the data sets were created according to EN15804 and the building contexts are taken into account.

LCA: Scenarios and additional technical information

Declared unit

Name	Value	Unit
Transport to the construction site (A4)		
Liters of fuel	0.00891	l/100 km
Transport distance	805	km
Capacity utilization	85	%
Installation in the building (A5)		
Auxiliary materials	0.004	kg
Maintenance (B2)		
Vacuum cleaning	7	1/week
Vacuum cleaning per RSL	105	1/RSL
Extraction cleaning	2	1/year
Extraction cleaning per RSL	30	1/RSL
Water consumption	1.93	kg/year
Electricity consumption	1.615	MJ/year
Cleaning agent	0.007	kg/year
Reference service life (RSL)		
RSL	15	years
End of Life		
Transport to disposal	32.2	km
Landfill	4.189	kg

ENVIRONMENTAL PRODUCT DECLARATION

Interface®

Interface Asia Pacific - Thailand
Modular Carpet on GlasBac®
Nylon 6 Styles

According to ISO 14025

LCA results

Description of the system boundary (X = included in LCA; MND = module not declared)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS (BEYOND THE SYSTEM BOUNDARY)
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement ¹⁾	Refurbishment ¹⁾	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	X	MND	MND	MND	MND	MND	MND	X	MND	X	MND

Results of the LCA - Environmental impact potentials

CML 2001 - Jan. 2016

	A1-A3	A4	A5	B2	C2	C4
GWP [kg CO2-Equiv.]	8.59E00	1.09E-01	3.41E-02	3.84E-01	4.10E-03	7.26E-02
ODP [kg R11-Equiv.]	9.54E-07	7.12E-13	6.63E-10	2.09E-09	2.69E-14	2.68E-12
AP [kg SO2-Equiv.]	3.82E-02	8.23E-04	1.19E-04	9.95E-04	3.11E-05	1.98E-04
EP [kg Phosphate-Equiv.]	4.89E-03	2.16E-04	5.40E-05	1.97E-04	8.16E-06	1.96E-04
POCP [kg Ethene-Equiv.]	4.61E-03	-3.52E-04	1.59E-05	7.15E-05	-1.33E-05	2.57E-05
ADPe [kg Sb-Equiv.]	1.72E03	1.65E-08	4.32E-09	6.38E-04	6.23E-10	1.39E-08
ADPf [MJ]	1.36E02	1.55E00	5.30E-01	3.27E00	5.84E-02	1.02E00

TRACI 2.1

	A1-A3	A4	A5	B2	C2	C4
GWP [kg CO2-Equiv.]	8.52E00	1.08E-01	3.35E-02	3.83E-01	4.09E-03	7.15E-02
ODP [kg CFC 11-Equiv.]	1.25E-06	7.58E-13	8.67E-10	2.28E-09	2.86E-14	2.85E-12
AP [kg SO2-Equiv.]	3.84E-02	1.12E-03	1.20E-04	1.05E-03	4.24E-05	2.08E-04
EP [kg N-Equiv.]	6.32E-03	8.79E-05	2.58E-05	2.80E-04	3.32E-06	9.42E-05
SFP [kg O3-Equiv.]	4.37E-01	2.55E-02	1.53E-03	1.58E-02	9.62E-04	3.47E-03

Caption: GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non fossil resources; ADPF = Abiotic depletion potential for fossil resources; SFP = Smog air

ENVIRONMENTAL PRODUCT DECLARATION

Interface®

Interface Asia Pacific - Thailand
Modular Carpet on GlasBac®
Nylon 6 Styles

According to ISO 14025

Results of the LCA - Resource use: declared unit and product

	A1-A3	A4	A5	B2	C2	C4
PERE [MJ]	1.95	0.025	-	1.02	0.000945	0.0729
PERM [MJ]	10.2	-	0.0209	0.0125	-	-
PERT [MJ]	12.2	0.025	0.0209	1.03	0.000945	0.0729
PENRE [MJ]	14	1.55	-	3.83	0.0587	1.06
PENRM [MJ]	157	-	0.565	0.908	-	-
PENRT [MJ]	171	1.55	0.565	4.74	0.0587	1.06
SM [kg]	3.44	-	-	-	-	-
RSF [MJ]	-	-	-	-	-	-
NRSF [MJ]	-	-	-	-	-	-
FW [m ³]	0.464	0.000314	2.31E-006	0.0018	1.19E-005	4.68E-006

Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non renewable secondary fuels; FW = Use of net fresh water
---------	---

Results of the LCA - Output flows and waste categories: declared unit and product

	A1-A3	A4	A5	B2	C2	C4
HWD [kg]	0.00253	1.99E-009	1.52E-009	2.31E-009	7.5E-011	6.04E-009
NHWD [kg]	0.17	5.25E-005	0.25	0.00257	1.98E-006	0.997
RWD [kg]	0.00451	2.6E-006	4.96E-006	0.000566	9.81E-008	1.62E-005
CRU [kg]	-	-	-	-	-	-
MFR [kg]	0.0177	-	-	-	-	0
MER [kg]	0	-	0	-	-	0
EEE [MJ]	-	-	-	-	-	-
EET [MJ]	-	-	-	-	-	-

Caption	HWD = Hazardous waste disposed; NHWD = Non hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy
---------	---

ENVIRONMENTAL PRODUCT DECLARATION

Interface®

Interface Asia Pacific - Thailand
Modular Carpet on GlasBac®
Nylon 6 Styles

According to ISO 14025

Results of the LCA - Product stage A1-A3 Global Warming Potential (GWP) for additional product yarn weights (ounces per square yard / grams per square meter)

	GWP [kg CO2-Equiv.]
12 oz. / 407 gr.	7.26
13 oz. / 441 gr.	7.43
14 oz. / 475 gr.	7.60
15 oz. / 509 gr.	7.76
16 oz. / 542 gr.	7.92
17 oz. / 575 gr.	8.09
18 oz. / 610 gr.	8.26
19 oz. / 644 gr.	8.43
20 oz. / 678 gr.	8.59
21 oz. / 712 gr.	8.76
22 oz. / 746 gr.	8.93
23 oz. / 780 gr.	9.09
24 oz. / 814 gr.	9.26
25 oz. / 848 gr.	9.43
26 oz. / 881 gr.	9.59
27 oz. / 915 gr.	9.76
28 oz. / 949 gr.	9.93
29 oz. / 983 gr.	10.09
30 oz. / 1017 gr.	10.26
31 oz. / 1051 gr.	10.43
32 oz. / 1085 gr.	10.59
33 oz. / 1119 gr.	10.76
34 oz. / 1153 gr.	10.93
35 oz. / 1187 gr.	11.09
36 oz. / 1220 gr.	11.26
37 oz. / 1254 gr.	11.42
38 oz. / 1288 gr.	11.59
39 oz. / 1322 gr.	11.76
40 oz. / 1356 gr.	11.93
41 oz. / 1390 gr.	12.09
42 oz. / 1424 gr.	12.26

LCA: Interpretation

The life cycle impacts of modular carpets are driven by the Product Stage and the impacts from this stage are driven by raw materials. Yarns and backing materials are the major contributors to impacts. Recycled polymers in both yarns and backings greatly reduce the impacts as compared to virgin petrochemically based materials previously used in Interface carpet manufacture.

References

ASTM E-648. Standard Test Method for Critical Radiant Flux of Floor-Covering Systems Using a Radiant Heat Energy Source. <http://www.astm.org/Standards/E648.htm>

ASTM E-662. Standard Test Method for Specific Optical Density of Smoke Generated by Solid Materials. <http://www.astm.org/Standards/E662.htm>

Carpet & Rug Institute. CRI Test Method 101. http://www.carpet-rug.org/technical_bulletins/0307_CRI_TM_101.pdf
Carpet & Rug Institute. Residential Customers Green Label / Green Label Plus. <http://www.carpet-rug.org/residentialcustomers/selecting-the-right-carpet-or-rug/green-label.cfm>

GaBi 7 (2016). Software-System and Databases for Life Cycle Engineering Copyright, TM. Stuttgart, Echterdingen

ISO 14040 (2006). Environmental management - Life cycle assessment Principles and framework

ISO 14044 (2006). Environmental management - Life cycle assessment Requirements and guidelines

Institut Bauen und Umwelt: Institut Bauen und Umwelt e.V., Berlin (pub.): Generation of Environmental Product Declarations (EPDs); General principles for the EPD range of Institut Bauen und Umwelt e.V. (IBU), 2013-04 www.bau-umwelt.de

PCR Part A: Institut Bauen und Umwelt e.V., Königswinter (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. April 2013 www.bau-umwelt.de

ISO 14025: DIN EN ISO 14025:2011-10: Environmental labels and declarations - Type III environmental declarations - Principles and procedures

EN 15804: EN 15804:2012-04+A1 2013: Sustainability of construction works - Environmental Product Declarations - Core rules for the product category of construction products