

Dolomite

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Dolomite			
Type	Tufted Plain Textured Loop Pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC3			
Total Thickness	6.9 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	4292001 Diamond	4292002 Crystal	4292003 Obsidian	4292004 Golden Beryl
	4292005 Rose Quartz	4292006 Amber	4292007 Pearl	4292008 Moonstone
	4292009 Aventurine	4292010 Malachite	4292011 Azurite	4292012 Lapis Lazuli
Method of laying	Monolithic Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465