



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

NY+LON Streets - Dover Street

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	NY+LON Streets - Dover Street			
Type	Tapestry Tufted Patterned Structured Loop Pile			
Yarn	100% Solution Dyed Nylon contains recycled content			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.3 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	9444001 Concrete Dot	9444002 Brown Dot	9444003 Iron Dot	9444004 Steel Dot
	9444005 Metal Dot	9444006 Graphite Dot	9444007 Slate Dot	9444008 Black Dot
Method of laying	Monolithic. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465