



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Elevation III

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Elevation III
Type	Microtufted loop pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	4.4 mm ± 0.5 mm
Size	50 x 50 cm - 5 m ² Box
Colourway	4199001 Colletino 4199002 Brocatello 4199003 Palissandra 4199004 Cioccolato 4199005 Fior Di Pesco 4199006 Ceppo Di Gre 4199007 Grigio Nilo 4199008 Portoro 4199009 Carrara 4199010 Jura 4199011 Valdeorras 4199012 Nero Maquina 4199013 Botticino 4199014 Romano Classico 4199015 Crema Luna 4199016 Opale Naturalea 4199017 Cipollino 4199018 Aqua Marina 4199019 Azuro Cielo 4199020 Zircona
Method of laying	Quarter Turn. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465