



## Equal Measure 551

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
<b>Base</b>	Please refer to Interface installation guide for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.
<b>Carpet Tiles</b>	
<b>Manufacturer</b>	Interface
<b>Product Reference</b>	Equal Measure 551
<b>Type</b>	Tufted Patterned Structured Loop Pile
<b>Yarn</b>	100% Recycled Solution Dyed Nylon
<b>Standard Backing</b>	CQuest™Bio
<b>BS EN 1307 classification</b>	
<b>Category</b>	Type 1
<b>Level of use class</b>	Heavy Contract, class 33
<b>Luxury rating class</b>	LC2
<b>Total Thickness</b>	7.4 mm ± 0.5 mm
<b>Size</b>	25 x 100 cm - 5 m <sup>2</sup> Box
<b>Colourway</b>	7887001 Cobblestone St.                      7887003 Main St.                      7887004 Hill St. 7887005 Broad St.                                  7887007 Union St.                      7887008 Oldtown St.
<b>Method of laying</b>	Herringbone, Ashlar. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465