

Flash Line [-CO₂]

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Flash Line			
Type	Microtuft Patterned Level Loop Pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	CQuest™BioX			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	5.7 mm ± 0.5 mm			
Size	25 x 100 cm standard size			
Colourway	4289001 Amber Flash	4289002 Cream Flash	4289003 Aqua Flash	4289004 Ivory Flash
	4289005 Grey Flash	4289006 Ruby Flash	4289007 Terracotta Flash	4289008 Olive Flash
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465