

Iridescence

Location	Heavy use for entrance and stairs in office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface LVT installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Luxury Vinyl Tiles				
Supplier	Interface			
Product Reference	Iridescence			
Type	High performance luxury vinyl tile			
Standard Backing	Sound Choice™ acoustic backing			
BS EN 651 classification				
Category	Heterogeneous luxury vinyl tile			
Level of use class	Class 33 heavy commercial / 42 general light industrial			
Total Thickness	4.5 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	A01901 Polar	A01902 Shadow	A01903 Clay	A01904 Night
	A01905 Herb	A01906 Wave	A01907 Frost	A01908 Ink
	A01909 Reef	A01910 Golden	A01911 Earth	A01912 Blossom
Method of laying	Non Directional			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465