



Touch & Tones 101

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Touch & Tones II 101			
Type	Level loop pile			
Yarn	100% Recycled Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.4 mm ± 0.5 mm			
Size	50 x 50 cm - 5 m ²			
Colourway	4174062 Biscuit	4174063 Mushroom	4174064 Coffee	4174065 Carbon
	4174066 Concrete	4174067 Stone	4174068 Iron	4174069 Anthracite
	4174070 Olive	4174071 Forest	4174072 Petrol	4174073 Sapphire
	4174074 Blush	4174075 Gold	4174076 Garnet	4174077 Terracotta
Method of laying	Monolithic. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465