



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Works Fluid

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
<b>Base</b>	Please refer to Interface installation guide for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
<b>Fabricated Underlay</b>	N/a. Carpet tiles to be adhered direct to the subfloor.
<b>Carpet Tiles</b>	
<b>Manufacturer</b>	Interface
<b>Product Reference</b>	Works Fluid
<b>Type</b>	Tufted Patterned Structured Loop Pile
<b>Yarn</b>	100% Solution Dyed Nylon
<b>Standard Backing</b>	CQuest™Bio
<b>BS EN 1307 classification</b>	
<b>Category</b>	Type 1
<b>Level of use class</b>	Heavy Contract, class 33
<b>Luxury rating class</b>	LC1
<b>Total Thickness</b>	7.1 mm ± 0.5 mm
<b>Size</b>	25 x 100 cm standard size, 5m <sup>2</sup> per box
<b>Colourway</b>	4285001 Ebony                      4285002 Storm 4285003 Concrete                  4285004 Dove 4285005 Shadow                   4285006 Taupe 4285007 Drizzle                    4285008 Denim
<b>Method of laying</b>	Ashlar & Herringbone Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#). For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465