



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

World Woven 860

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
Base	Please refer to Interface installation guide for details of suitability.		
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
Fabricated Underlay	Should be laid where required over existing timber bases.		
Carpet Tiles			
Manufacturer	Interface		
Product Reference	World Woven 860		
Type	Tufted Patterned Level Loop Pile		
Yarn	100% Recycled Solution Dyed Nylon		
Standard Backing	CQuest™Bio		
BS EN 1307 classification			
Category	Type 1		
Level of use class	Heavy Contract, class 33		
Luxury rating class	LC1		
Total Thickness	5.4 mm ± 0.5 mm		
Size	25 x 100 cm - 5 m ² Box		
Colourway	8109001 Linen Tweed	8109002 Flannel Tweed	8109003 Charcoal Tweed
	8109004 Black Tweed	8109005 Brown Tweed	8109006 Natural Tweed
	8109007 Raffia Tweed	8109008 Sisal Tweed	
Method of laying	Herringbone, Ashlar. Install using TacTiles® for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465