

## Yuton 105

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	N/a. Carpet tiles to be adhered direct to the subfloor.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Yuton 105			
<b>Type</b>	Tufted Patterned Structured Loop Pile			
<b>Yarn</b>	100% Solution Dyed Nylon			
<b>Standard Backing</b>	CQuest™Bio			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC1			
<b>Total Thickness</b>	5.9 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm standard size			
<b>Colourway</b>	4159014 Coal	4159015 Lead	4159016 Urban	4159017 Overcast
	4159018 Fossil	4159019 Ice	4159020 Truffle	4159021 Biscuit
<b>Method of laying</b>	Monolithic and Ashlar. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465