

## Superflor II

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	N/a. Carpet tiles to be adhered direct to the subfloor.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Superflor II			
<b>Type</b>	Coarse Fibre Needlefelt tile			
<b>Yarn</b>	70% Solution Dyed Nylon, 20% Polyester, 10% Polypropylene			
<b>Standard Backing</b>	CQuest™Bio			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC1			
<b>Total Thickness</b>	6.9 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm standard size			
<b>Colourway</b>	4308001 Siberian Frost II	4308002 Grey II	4308003 Raven II	4308004 Mid Brown II
	4308005 Buffalo II	4308006 Oceanus II	4308007 Seville Passion II	4308008 Irish Coffee II
	4308009 Yippee II	4308010 Primavera II		
<b>Method of laying</b>	Non Directional Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465