

Woven Gradience WG100

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Woven Gradience WG100			
Type	Tufted Patterned Structured Loop Pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.8 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	4306001 Ink	4306002 Charcoal	4306003 Stone	4306004 Chalk
	4306005 Rose	4306006 Emerald	4306007 Ocean	4306008 Forest
	4306009 Terracotta	4306010 Lagoon	4306011 Sage	4306012 Sunrise
Method of laying	Monolithic, Brick, Ashlar Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465