

Woven Gradience WG200

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Woven Gradience WG200			
Type	Tufted Patterned Structured Loop Pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.8 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	4307001 Charcoal/Ink	4307002 Stone/Charcoal	4307003 Pearl/Stone	4307004 Ink/Rose
	4307005 Ink/Emerald	4307006 Charcoal/Ocean	4307007 Charcoal/Forest	4307008 Stone/Terracotta
	4307009 Stone/Lagoon	4307010 Pearl/Sage	4307011 Pearl/Sunrise	
Method of laying	Monolithic, Brick, Ashlar Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465